



1. ALL RESISTORS IN OHMS AND 0.5W.
2. ALL CAPACITORS IN MICROFARADS UNLESS OTHER PREFIX MARKED, THEN REPLACE PREFIX (MICRO) IN UNIT (MICROFARAD) WITH MARKED PREFIX. ALL CAPACITORS 25V (MINIMUM VOLTAGE RATING) UNLESS MARKED OTHERWISE.
3. ALL VOLTAGES IN VOLTS.
4. ALL POTS , R19 TO R22: 100KB.
5. TRANSISTOR Q1: MPSA13.
6. TRANSISTOR Q2: 2N5088.
7. TRANSISTOR Q3: 2N5086.
8. ZENER DIODE D1: 1N5244B.
9. LAST REFERENCED DESIGNATION ON PC. BOARD:
R22, C10, Q3, D1, J4, P3.

RIC Rickenbacker International Corp.
 3895 S. Main Street
 Santa Ana, Ca. 92707
 Tel: 714-545-5574 Fax: 714-754-0135

COMPONENT LAYOUT, PREAMP RB30, RB60, RB120

SCALE	x1	CHECKED BY	J. HALL	DRAWN BY	K. MASCARENHAS
DATE	3/8/89				
SIZE	B	DRAWING NO.			DE0006