

Rocket Fuzz - Parts and Pieces

Parts List

Qty	Description	Supplier	Part number	Price Each
1	- 100 ohm, 1/4W resistor	Mouser	29SJ250-100	0.07
1	- 1.2K ohm, 1/4W resistor	Mouser	29SJ250-1.2K	0.07
4	- 10K ohm, 1/4W resistor	Mouser	29SJ250-10K	0.07
1	- 47K ohm, 1/4W resistor	Mouser	29SJ250-47K	0.07
1	- 470K ohm, 1/4W resistor	Mouser	29SJ250-470K	0.07
1	- 1M ohm, 1/4W resistor	Mouser	29SJ250-1M	0.07
2	- 47uF/16V electro cap	Mouser	140-XRL16V47	0.07
4	- 0.1uF film capacitor	Mouser	140-PF1H104K	0.24
3	- Tuning capacitors - see text	Mouser	140-PF1H104K	0.24
1	- 4.7K trimmer potentiometer	Mouser	323-409H-5K	0.61
3	- 2N5088 transistor or Equivalent	Mouser	610-2N5088	0.26
1	- 50K linear pot, 16mm	Mouser	313-1000-50K	1.24
1	- 10K linear pot, 16mm	Mouser	313-1000-10K	1.24
1	- 10K audio pot, 16mm	Mouser	313-4000-10K	1.74
1	- stereo 1/4" jack (input)	Mouser	502-112B	1.96
1	- mono 1/4" jack (output)	Mouser	501-111	1.88
1	- battery clip	Mouser	12BC126	0.39
1	- Box - I prefer Hammond 1590BB	Mouser	546-1590BB	10.40
3	- knobs			
1	- Stomp switch	Where you find them!	\$2.50 to \$16.00	

Miscellaneous hookup wire, solder, etc.

Building it:

Start 0.1uF in the positions noted for tuning the response of the circuit, then follow Aron's advice to tune it to your taste.

In building the board, first figure out how you will mount the board in your box, and either mark and drill holes if you prefer the screw-down standoffs (ugh! shudder!!) or place the adhesive standoffs or velcro :-)) with the bare board - it's much easier to do the mechanical work before you populate the board. See <http://www.geofex.com> in the tips and tricks section to see a sketch of how this board would fit in a Hammond 1590BB.

Once the holes are cut and the box is laid out, start populating the board. For easiest assembly, work from the lowest to the highest components. First solder in resistors.

If you make many effects boards, it's handy to get the Mouser 5166-801 lead bender, (\$2.94) as this will let you quickly and accurately bend resistor leads so they just drop in the holes on the board. All GEO boards mount the resistors in exactly the same way. You can also whack a bit of wood or plexiglass or other plastic into a handy lead bender. This saves a lot of time.

Once the resistors are in, put in the transistors, and finally the capacitors. Work slowly and make sure your solder joints are good. The Rocket board has been designed to make solder bridges less likely, but good soldering will pay off handsomely when you start debugging, as nothing will make up for cold, poorly made solder joints.

Once the board is populated and you are happy with the way it looks, solder in the hookup wire leads. I find it helpful to cut the lead wires approximately to length, strip both ends and then solder them all into the circuit board before trying to solder them to the controls and switches. I have a "secret weapon" for wiring up effects - I drilled 3/8" and 1/2" holes in a block of 2"x8" lumber scrap. This lets me stick the pots, jacks and switches outer ends into the holes and leave their lugs exposed so I can lay the board in the middle and just solder the wires, then put the whole thing into the box at once - no burned fingers and/or wires trying to solder wires while the board is in the box.

Happy Building!!

R.G.